### **US Office**

1712 Pioneer Ave., Ste 500 Cheyenne WY 82001

www.DuraFastLabel.com

### **Canadian Office**

53 Queen's Plate Drive, Unit 2 Toronto ON M9W-6P1

(\*) www.**Dura**FastLabel.ca

## R510W

**Durable White Resin** 



### **Product Description**

Designed with our specially formulated backcoat technology for printhead protection, this ribbon has unmatched scratch and solvent resistance. It is extremely resistant to ethanol and isopropanol and is industry leader in edge definition for clean, durable and dense barcodes.

### Standard Colors



### **Recommended Applications**









Beverage



Logistics



### **Product Features**

FDA (indirect food contact)	$\checkmark$
Halogen-free	$\checkmark$
High-density	$\checkmark$
Printhead Protection	$\checkmark$
Proprietary Backcoat	$\checkmark$
Scratch Resistant	$\checkmark$
Smudge Resistant	$\checkmark$
Solvent Resistant	✓





### **US Office**

1712 Pioneer Ave., Ste 500 Cheyenne WY 82001



### **Canadian Office**

53 Queen's Plate Drive, Unit 2 Toronto ON M9W-6P1

(\*) www.**Dura**FastLabel.ca

## R510W

**Durable White Resin** 

# **Product Specifications**

### Wax

Half Inch

MP Wax

TR3021 Red

TR3022 Blue

TR3023 Green

TR4085plus® Premium Resin-Enhanced

#### Way/Racin

M260 Ultra Durable

TRX-50 General Purpose

TRX-55 Premium

### Resin

R300 General Purpose

R316 Specialty

R395 Textile

R510C Durable Color

R510HF Ultra Durable

R510W Durable White

TR3370 High Opacity White TR4070 Classic

VR3 01 Durable Metallic Color

### Near Edge

M295 Plus Specialty Wax/Resin

M295C Specialty Wax/Resin Color

R390 Resin

R396 High Speed Durable Resin

TR4500 Premium Wax/Resin

### Recommended Substrates

Economy Synthetics	Chrome Polyester Clear Polyester Gloss Silver Polyester Matte Silver Polyester
Specialty Materials	PVC Shrink Tubing

### **Ribbon Properties**

Ink	Resin
Color	White
Base Film Thickness	$4.8\pm0.3\mu$
Ink Thickness	$4.5\pm0.2\mu$
Total Thickness	$9.3\pm0.5\mu$
Ink Transfer Temperature	Uncoated Tag 246°C (475°F)





