US Office

1712 Pioneer Ave., Ste 500 Cheyenne WY 82001

www.**Dura**FastLabel.com

Canadian Office

53 Queen's Plate Drive, Unit 2 Toronto ON M9W-6P1

www.**Dura**FastLabel.ca

TR3021

General Purpose Red Wax



Product Description

Based on our proven wax technology, these quality red ribbons expand your possibilities while providing excellent print clarity and high smudge resistance when black just isn't enough. These ribbons are also specially formulated with an exclusive backcoat technology for printhead protection.

Standard Colors



Red PMS 1787C*

Pantone® Matching System (PMS) $^*\mathsf{Colors}$ may vary by substrate

Recommended Applications









Compliance

Specifications subject to change without notice. ©2019 by Sector Nine Distribution Limited

Inventory & Logistics

Product Features

FDA (indirect food contact)	\checkmark
High-density	\checkmark
High-speed	\checkmark
Printhead Protection	\checkmark
Proprietary Backcoat	\checkmark
Smudge Resistant	✓





US Office

1712 Pioneer Ave., Ste 500 Cheyenne WY 82001



Canadian Office

53 Queen's Plate Drive, Unit 2 Toronto ON M9W-6P1

(*) www.**Dura**FastLabel.ca

TR3021

Product Specifications

General Purpose Red Wax

W	ax	
••	чл	

Half Inch

MP Wax

TR3021 Red TR3022 Blue

TR3023 Green

TR4085plus® Premium Resin-Enhanced

Wax/Resin

M260 Ultra Durable

TRX-50 General Purpose

TRX-55 Premium

Resin

R300 General Purpose

R316 Specialty

R395 Textile

R510C Durable Color

R510HF Ultra Durable

R510W Durable White

TR3370 High Opacity White

TR4070 Classic

VR3 01 Durable Metallic Color

Near Edge

M295 Plus Specialty Wax/Resin

M295C Specialty Wax/Resin Color

R390 Resin

R396 High Speed Durable Resin

TR4500 Premium Wax/Resin

Recommended Substrates

Paper	Coated Paper Coated Tag Uncoated Paper Uncoated Tag
Economy Synthetics	Polyethylene Polyolefin Polypropylene Synthetic Paper
Specialty Materials	Top-Coated Vinyl Tyvek® Tyvek Brillion®

Ribbon Properties

Ink	Wax
Color	Re d
Base Film Thickness	$4.8\pm0.3\mu$
Ink Thickness	$3.6 \pm 0.2 \mu$
Total Thickness	$8.4\pm0.5\mu$
Ink Transfer Temperature	Uncoated Tag 79°C (175°F)



