# **US Office**

1712 Pioneer Ave., Ste 500 Cheyenne WY 82001

www.**Dura**FastLabel.com

# **Canadian Office**

53 Queen's Plate Drive, Unit 2 Toronto ON M9W-6P1

www.**Dura**FastLabel.ca

# TR4085plus®

Premium Resin-Enhanced Wax



# **Product Description**

The industry's leading wax product since its introduction to the market in November 2000, this ribbon features a SmoothCoat® backcoat and a 4 Million Linear Inch Guarantee. This unique ink formulation dissipates static and is versatile enough to print on a wide variety of labelstocks.

# **Recommended Applications**











Beverage

Beauty

Inventory & Logistics

Pharmaceutical



Specifications subject to change without notice. ©2019 by Sector Nine Distribution Limited

# **Product Features**

4 Million Linear Inch Guarantee	✓
Anti-static	$\checkmark$
FDA (indirect food contact)	$\checkmark$
Halogen-free	$\checkmark$
High-density	$\checkmark$
High-speed	$\checkmark$
Proprietary Backcoat	$\checkmark$
Scratch Resistant	$\checkmark$
Smudge Resistant	$\checkmark$





### **US Office**

1712 Pioneer Ave., Ste 500 Cheyenne WY 82001

www.DuraFastLabel.com

### Canadian Office

53 Queen's Plate Drive, Unit 2 Toronto ON M9W-6P1

(\*) www.**Dura**FastLabel.ca

# TR4085plus®

# **Product Specifications**

Premium Resin-Enhanced Wax

### Wax

Half Inch

MP Wax

TR3021 Red

TR3022 Blue

TR3023 Green
TR4085plus® Premium Resin-Enhanced

#### Wax/Resin

M260 Ultra Durable

TRX-50 General Purpose

TRX-55 Premium

### Resin

R300 General Purpose

R316 Specialty

R395 Textile

R510C Durable Color

R510HF Ultra Durable

R510W Durable White

TR3370 High Opacity White

TR4070 Classic

VR3 01 Durable Metallic Color

# Near Edge

M295 Plus Specialty Wax/Resin

M295C Specialty Wax/Resin Color

R390 Resin

R396 High Speed Durable Resin

TR4500 Premium Wax/Resin

### Recommended Substrates

Paper	Coated Paper Coated Tag Flood-coated Gloss Uncoated Paper Uncoated Tag
Economy Synthetics	Kimdura® Polyart® Polyethylene Polyolefin Polypropylene Synthetic Paper UV Varnished Labels Valeron®

# **Ribbon Properties**

Ink	Wax (resin-enhanced)
Color	Black
Base Film Thickness	$4.8\pm0.3\mu$
Ink Thickness	$3.2 \pm 0.2 \mu$
Total Thickness	$8.0\pm0.5\mu$
Ink Transfer Temperature	Uncoated Tag 66°C (150°F)



Specifications subject to change without notice.

©2019 by Sector Nine Distribution Limited

